

A one-component liquid paint remover designed to aid preparation activities prior to paint application. RTB-1314-R is used to clean the substrate and remove any old layers of paint quickly and with relative ease.

### USES

Recommended Uses      Used as paint remover for Baking Enamels and Alkyd, Polyurethane, Vinyl and Air-Drying coatings.

### CHEMICAL COMPOSITION

Chemical Composition	Ketones and Other Paint Penetrating Solvents	Solid Content	---
Number of Component(s)	1 Component		
Curing Mechanism	---	Flash Point	5°C (41°F)

### PHYSICAL PROPERTIES

Finish	Clear
Colour	Liquid
Specific Gravity	0.92 ± 0.03 gr/cm <sup>3</sup>

### APPLICATION DETAILS

Application Process      Use a small amount of liquid on the surface as a test to determine the cleaning strength of the liquid relative to the amount of contaminants present on the substrate. Apply an appropriate amount of the liquid onto areas already treated with RTB-1313-R (Ronass Paint Remover – Gel) using a brush, removing any old paint or other contaminants in the process. In the event that a noticeable amount of paint remains, repeat the process. To ensure that no paint remains, use a plastic or wire brush.

Method of Application      Special Spreading Knife | Brush | Steel Brush | Plastic Brush | Scraper

Application Limits	Relative Humidity	Min. ---	Max. ---
	Temperature	Min. +5°C	Max. +35°C
	Substrate Temperature*	Min. +5°C	Max. +35°C

Recommendations      Clean tools thoroughly before and immediately after use with cleaning solver T-111.

### PACKING, STORAGE AND SAFETY

Packing      1 Litre Containers (1 kgs. Net)

Storage Conditions      To be stored in cool and dry conditions in original sealed containers.

Shelf Life      At least 12 months after delivery in original sealed containers and proper storage conditions with temperature of 25°C.

Safety      This product contains organic solvents and flammable materials. Keep away from sparks, fires, electrical cables and equipments, direct sunshine and out of children's reach.

Protect skin, eyes, and avoid prolonged breathing of solvent vapor during application. Use with adequate ventilation.