



Health	3
Fire	0
Reactivity	0
Personal Protection	

SECTION 1 – MATERIAL IDENTIFICATION

A)	Trade / Material Name	Epoxy Coating	
B)	Description	Primer, intermediate or finish coat in multi-layered coating systems for steel structures and metal surfaces, or as a single coating system in maintenance operations	
C)	Product Code(s)	RTB-443-A	
D)	Manufacturer Name	Ronass Chemical Producing Co.	
E)	Manufacturer Information	#95 Ghaem Magham Avenue, Tehran, Iran	
		Tel: (+98-21) 88307248-9	
		Fax: (+98-21) 88305965	
		www.ronass.com info@ronass.com	
F)	MSDS Preparation Date	July 17, 2018	

SECTION 2 – HAZARDOUS INGREDIENTS

Percentage	Max. Legal Limit
Max. 28% (By Weight)	N.A.
Max. 45% (By Weight)	N.A.
Max. 27% (By Weight)	N.A.
	Max. 28% (By Weight) Max. 45% (By Weight)

SECTION 3 – PHYSICAL DATA

ronass.com

Ş

A) Appearance and Odor	Coloured Liquid Light Odor
B) V.O.C.	Max. 15%
C) Viscosity	Max. 103 KU
D) pH Range	5.8 – 7
E) Water Solubility	No
F) Specific Gravity	$1.65 \pm 0.05 \text{ gr/cm3}$ (Component A)
	1.50 ± 0.05 gr/cm3 (After Mixing)
G) Flash Point	28°C
H) Boiling Point	128°C
I) Melting / Freezing Point	N.A.

W

ĴÅ.

R

Œ

(CA



SECTION 4 – STABILITY AND REACTIVITY DATA

MATERIAL IS STABLE | HAZARDOUS POLYMERIZATION CANNOT OCCUR

A) Chemical Incompatibilities Water, oil and ir	norganic compounds
B) Conditions to Avoid Excessive heat, switchboards	, sparks, open flame, high voltage power lines /

- C) Hazardous Decomposition Product(s)
- D) Hazardous Polymerization Product(s)

Carbon Monoxide, Carbon Dioxide, Organic Solvent Vapor
 None

SECTION 5 – LEAK AND DISPOSAL PROCEDURES

- A) Spill and / or Leak Procedures
- B) Waste Management / Disposal

Contain and collect with absorbent material In accordance with state and provincial regulations

C) Large Spills

A) Summary of Risks

Remove all sources of ignition; ventilate area; Contain spill with inert absorbent, or mop up

Contact may cause eye irritation; prolonged contact with skin

SECTION 6 – FIRST AID MEASURES

THIS PRODUCT IS NOT CONSIDERED A CARCINOGEN BY OSHA, NTP, IARC

		can cause irritation; excessive inhalation can cause dizziness and headache
B)	Medical Conditions That May Be Aggravated by Contact	Pre-existing disorders of the liver or kidneys, eyes, skin, or respiratory system may be aggravated by exposure to this product
C)	Primary Entry Route(s)	Eye contact; skin contact; respiratory and ingestion systems
D)	Acute Effect(s)	Eye and skin irritation; dizziness; headache and nausea from excessive inhalation
E)	Chronic Effect(s)	Aspiration of product into lungs (due to vomiting) can cause chemical pneumonitis, which can be fatal
F)	Signs and Symptoms of Overexposure	
	✤ Eye Contact	Redness; tearing; blurred vision
	 Skin Contact 	Redness; blistering
	 ♦ Inhalation 	Dizziness; headache
	 ✤ Ingestion 	Nausea; cramps; diarrhea
G)	First Aid	
	✤ Eye Contact	Flush with plenty water for 10 minutes; get medical advice
	✤ Skin Contact	Wash with soap and cool water; seek medical attention if irritation persists
	 ♦ Inhalation 	Move to an area with fresh air
	 ✤ Ingestion 	Do not induce vomiting; call a physician immediately for instructions

ass

C O



SECTION 7 – FIRE EXTINGUISHING MEASURES

A) Flash Point and Method	28°C		
B) Autoignition Temperature	N.A.		
C) Flammable Limits in Air	12% (LEL)	25% (UEL)	
D) Extinguishing Media	Water fog; dry chemic	Water fog; dry chemical; CO2 foam; sand	
E) Special Firefighting Procedures	Protective equipment and clothing; respirator		
F) Unusual Fire and Explosion	Do not spray near open flame, hot engines or devices which may spark		

Lingering vapors given off by the product's aerosol spray may support combustion; adequate ventilation is essential when using this product around potential sources of ignition

SECTION 8 – SPECIAL PROTECTION INFORMATION

A)	Personal Protective Equipment		
	*	Goggles	Safety glasses; eye wash station available
	*	Gloves	Rubber Gloves
	*	Respirator	Respirator mask in confined areas or emergency situations
B)	Wor	kplace Considerations	
	*	Fire Extinguisher	Always keep a number of ABC fire extinguishers and sand buckets within the vicinity of the workplace or storage area
	*	Ventilation	Provide sufficient mechanical (general and/or local) ventilation to maintain exposure below TLV
C)	C) Safety Stations		
	*	Eye Contact	Eye wash stations
	*	Contaminated Equipment and Clothing	Wash before reusing

SECTION 9 - STORAGE AND HANDLING

A) Storage Conditions

Keep away from sources capable of igniting product container or packaging materials; store in well ventilated, cool and dry conditions Handle with care; store indoors

- B) Special Handling / Storage
- C) Shelf Life

At Least 12 Months

ww.ronass.com



SECTION 10 – TRANSPORTATION INFORMATION

A) Shipping Classification	3.3
B) WHMIS Classification	С
C) UN Number	1866
D) Packaging	20 L (Metal Container)

THIS PRODUCT MSDS PROVIDES HEALTH AND SAFETY INFORMATION. THE PRODUCT IS TO BE USED IN APPLICATIONS CONSISTENT WITH COMPANY LITERATURE AND PRODUCT DIRECTIONS. INDIVIDUALS HANDLING THIS PRODUCT SHOULD HAVE ACCESS TO THIS INFORMATION. FOR ANY OTHER USES, EXPOSURES SHOULD BE EVALUATED SO THAT APPROPRIATE HANDLING PRACTICES AND TRAINING PROGRAMS CAN BE ESTABLISHED TO ENSURE SAFE WORKPLACE OPERATIONS. PLEASE CONTACT RONASS CHEMICAL PRODUCING CO. FOR FURTHER INFORMATION.

www.ronass.com