



Health	3
Fire	0
Reactivity	0
Personal Protection	

SECTION 1 - MATERIAL IDENTIFICATION

A) Trade / Material Name Two-Pack Polyurethane Coating

B) Description Finish coat for maintenance works and protective coating systems

C) Product Code(s) RTB-838-A

D) Manufacturer Name Ronass Chemical Producing Co.

E) Manufacturer Information #95 Ghaem Magham Avenue, Tehran, Iran

> Tel: (+98-21) 88307248-9 Fax: (+98-21) 88305965

www.ronass.com | info@ronass.com

F) MSDS Preparation Date July 17, 2018

SECTION 2 – HAZARDOUS INGREDIENTS

Name **Percentage** Max. Legal Limit **Organic Solvents** Max. 35% (By Weight) N.A. N.A. **Total Pigments** Max. 40% (By Weight) **Solid Resins** Max. 30% (By Weight) N.A.

SECTION 3 - PHYSICAL DATA

A) Appearance and Odor Coloured Liquid | Light Odor

B) V.O.C. Max. 30% C) Viscosity Max. 120 KU 5.8 - 7D) pH Range E) Water Solubility

F) Specific Gravity 1.40 ± 0.10 gr/cm3 (Component A)

No

 1.30 ± 0.10 gr/cm³ (After Mixing)

28°C G) Flash Point H) Boiling Point 128°C **Melting / Freezing Point** N.A.

Ronass MSDS





SECTION 4 - STABILITY AND REACTIVITY DATA

MATERIAL IS STABLE | HAZARDOUS POLYMERIZATION CANNOT OCCUR

A) Chemical Incompatibilities Water, oil and inorganic compounds

B) Conditions to Avoid Excessive heat, sparks, open flame, high voltage power lines /

switchboards

C) Hazardous Decomposition Product(s) Carbon Monoxide, Carbon Dioxide, Organic Solvent Vapor

D) Hazardous Polymerization Product(s) None

SECTION 5 – LEAK AND DISPOSAL PROCEDURES

A) Spill and / or Leak Procedures Contain and collect with absorbent material

B) Waste Management / Disposal In accordance with state and provincial regulations

C) Large Spills Remove all sources of ignition; ventilate area; Contain spill with

inert absorbent, or mop up

SECTION 6 - FIRST AID MEASURES

THIS PRODUCT IS NOT CONSIDERED A CARCINOGEN BY OSHA, NTP, IARC

A) Summary of Risks Contact may cause eye irritation; prolonged contact with skin

can cause irritation; excessive inhalation can cause dizziness

and headache

B) Medical Conditions That May Be

Aggravated by Contact

Pre-existing disorders of the liver or kidneys, eyes, skin, or respiratory system may be aggravated by exposure to this

product

C) Primary Entry Route(s) Eye contact; skin contact; respiratory and ingestion systems

D) Acute Effect(s) Eye and skin irritation; dizziness; headache and nausea from

excessive inhalation

E) Chronic Effect(s) Aspiration of product into lungs (due to vomiting) can cause

chemical pneumonitis, which can be fatal

F) Signs and Symptoms of Overexposure

Eye Contact Redness; tearing; blurred vision

Skin Contact Redness: blistering Inhalation Dizziness; headache Nausea; cramps; diarrhea

Ingestion

G) First Aid

❖ Eye Contact Flush with plenty water for 10 minutes; get medical advice Skin Contact Wash with soap and cool water; seek medical attention if

irritation persists

Inhalation Move to an area with fresh air

Ingestion Do not induce vomiting; call a physician immediately for

instructions





















SECTION 7 - FIRE EXTINGUISHING MEASURES

A) Flash Point and Method 28°C B) Autoignition Temperature N.A.

25% (UEL) C) Flammable Limits in Air 12% (LEL) D) Extinguishing Media Water fog; dry chemical; CO2 foam; sand E) Special Firefighting Procedures Protective equipment and clothing; respirator

F) Unusual Fire and Explosion Do not spray near open flame, hot engines or devices which

may spark

Lingering vapors given off by the product's aerosol spray may support combustion; adequate ventilation is essential when using this product around potential sources of ignition

SECTION 8 - SPECIAL PROTECTION INFORMATION

A) Personal Protective Equipment

Goggles Safety glasses; eye wash station available

Gloves Rubber Gloves

❖ Respirator Respirator mask in confined areas or emergency situations

B) Workplace Considerations

❖ Fire Extinguisher Always keep a number of ABC fire extinguishers and sand

buckets within the vicinity of the workplace or storage area

Provide sufficient mechanical (general and/or local) ventilation Ventilation

to maintain exposure below TLV

C) Safety Stations

Eye Contact Eye wash stations Contaminated Equipment and Wash before reusing

Clothing

SECTION 9 - STORAGE AND HANDLING

Keep away from sources capable of igniting product container A) Storage Conditions

or packaging materials; store in well ventilated, cool and dry

conditions

Handle with care; store indoors B) Special Handling / Storage

C) Shelf Life At Least 12 Months





















SECTION 10 - TRANSPORTATION INFORMATION

A) Shipping Classification 3.3 С B) WHMIS Classification C) UN Number 1866

20 L (Metal Container) D) Packaging

THIS PRODUCT MSDS PROVIDES HEALTH AND SAFETY INFORMATION. THE PRODUCT IS TO BE USED IN APPLICATIONS CONSISTENT WITH COMPANY LITERATURE AND PRODUCT DIRECTIONS. INDIVIDUALS HANDLING THIS PRODUCT SHOULD HAVE ACCESS TO THIS INFORMATION. FOR ANY OTHER USES, EXPOSURES SHOULD BE EVALUATED SO THAT APPROPRIATE HANDLING PRACTICES AND TRAINING PROGRAMS CAN BE ESTABLISHED TO ENSURE SAFE WORKPLACE OPERATIONS. PLEASE CONTACT RONASS CHEMICAL PRODUCING CO. FOR FURTHER INFORMATION.









